# Diaphragm Probe Seals Male Thread, Model 970.10 Male Running Nut, Model 970.11 Female Union Nut, Model 970.12

WIKA Data Sheet DS 97.01

### **Applications**

- For flowing, heterogeneous media
- Suitable for high pressures up to 1600 bar

### **Special features**

- Compact size
- Oval capsule sensor with internal support for stabilization
- Immersed directly in the medium



Fig. left:Male Pipe Thread, Model 970.10Fig. centre:Male Running Nut, Model 970.11Fig. right:Female Union Nut, Model 970.12

### Options

#### **Process connection**

- Model 970.10: G ¾ B, M20 x 1.5 male
- Model 970.11: G ¾ B, M20 x 1.5 male
- Model 970.12: G ¾, G 1 female

#### **Capsule sensor**

Dimension: 100 x 18 x 7 mm (requires minimum ¾ in. process connection)

#### Instrument connection

- Capillary (welded with body) and gauge adapter G <sup>1</sup>/<sub>2</sub> female to fit surface mounting bracket complete of stainless steel
- Cooling tower (for directly mounted gauge when fluid temperature > 100 °C)

Page 1 of 2



## Description

#### **Process connection**

Stainless steel 1.4571 Model 970.10: G ½ B male thread Model 970.11: G ½ B male running nut Model 970.12: G ½ female union nut

### Pressure rating

PN 600

#### **Pressure ranges** 0 ... 10 to 0 ... 600 bar

Capsule sensor Stainless steel 1.4571, welded with body Dimension: 75 x 13 x 6 mm

### Instrument connection

Stainless steel 1.4571, G 1/2 female per EN 837-1

WIKA Data Sheet DS 97.01 · 05/2008

## **Dimensions in mm**

### Model 970.10 with male thread



## Model 970.11 with male running nut



### Model 970.12 with union nut



| Model  | Dimensions in mm |    |    |   |    |     |    |   |     | Weight |
|--------|------------------|----|----|---|----|-----|----|---|-----|--------|
|        | G                | 1  | D  | s | SW | L   | В  | b | н   | in kg  |
| 970.10 | G ½ B            | 20 | 28 | - | 30 | 75  | 13 | 6 | 125 | 0.25   |
|        | M20 x 1.5 male   | 20 | 28 | - | 30 | 75  | 13 | 6 | 125 | 0.25   |
|        | G 3⁄4 B          | 22 | 35 | - | 36 | 100 | 18 | 7 | 152 | 0.40   |
| 970.11 | G ½ B            | 22 | 18 | 6 | 27 | 75  | 13 | 6 | 155 | 0.30   |
|        | G 3⁄4 B          | 24 | 24 | 6 | 32 | 100 | 18 | 7 | 180 | 0.40   |
| 970.12 | G 1⁄2            | 16 | -  | - | 27 | 75  | 13 | 6 | 155 | 0.30   |
|        | G 3⁄4            | 18 | -  | - | 32 | 100 | 18 | 7 | 180 | 0.40   |
|        | G 1              | 18 | -  | - | 41 | 100 | 18 | 7 | 180 | 0.50   |

1037196,01

## **Ordering information**

Model / Process connection / System fill fluid / Assembly on pressure measuring instrument model... / Process conditions as per questionnaire

Modifications may take place and materials specified may be replaced by others without prior notice. Specifications and dimensions given in this leaflet represent the state of engineering at the time of printing.

Page 2 of 2

WIKA Data Sheet DS 97.01 · 05/2008



WIKA Alexander Wiegand GmbH & Co. KG Alexander-Wiegand-Straße 30 63911 Klingenberg/Germany Tel. (+49) 9372/132-0 (+49) 9372/132-406 Fax E-mail info@wika.de www.wika.de